VIKING ACCESS SYSTEMS

SLEEK AND EFFICIENT SWING GATE AUTOMATION



residential and commercial



CULUS LISTED 18TC UL 325 UL 991

Class I, Class II, Class III, and Class IV Vehicular Gate Operator

G-5™ PRODUCT INFORMATION AND SPECIFICATIONS

With its compact, low profile design and the power to support 700 lbs of weight along with gate lengths of up to 16 feet, the Viking G-5™ will revolutionize the idea of gate operation. The G-5™ is capable of continuous cycles operation at 24V DC, converted directly from an AC line. The battery back-up provides up to 400 cycles of operation with a maximum capacity gate. This operator is UL Listed 18TC UL325 and UL991.



Adjustable timer for automatic close

On-board lightening protection



Adjustable positive stop





Easy access to limit switch



800.908.0884 vikingaccess.com



Operational Voltage ... 24 VDC with 1/2 H.P. Motor

Main Power Source ... 120 / 220 VAC Single Phase

Battery ... 7 AmpHr 12 VDC x 2

Max Gate Capacity ... 700 lbs. 16'

Max Operating Speed ... 16-18 seconds per 90°

Battery Backup Operation ... 400 Full Cycles (600 lbs. / 12' gate)

Max Duty Cycle ... 100% Continuous Cycle

Operating Temperature ... - 4° F to + 158° F

3 YEAR RESIDENTIAL / 2 YEAR COMMERCIAL WARRANTY