VIKING ACCESS SYSTEMS

HIGH TRAFFIC COMMERCIAL GATE SOLUTIONS





residential and commercial


SLIDE GATE OPERATOR

Class I, Class II, Class III, and Class IV Vehicular Gate Operator

H-10™ PRODUCT INFORMATION AND SPECIFICATIONS

The H-10[™] gate operator has the capacity to operate slide gates up to 2000 lbs. and 45 feet in length at 100% duty cycle under extreme conditions. It's efficient mechanism provides a solution for high traffic commercial slide gate applications. The Viking H-10[™] gate operator offers efficiency and technology combined in a single package. This operator is UL Listed 18TC UL325 and UL991.







Innovative Fine Tune Adjustment for the end of gate travel (down to 1/8")



Soft-stop - Soft-start with Intelligent Obstruction Detection



Standard loop rack

Built in optional auto-open feature in case of power failure

120/220 VAC single phase power source

Fail-Safe / Fail-Secure

Back-driveable unit features direct drive mechanism



800.908.0884 vikingaccess.com



Operational Voltage ... 24 VDC with 1 H.P. Motor

Main Power Source ... 120 / 220 VAC Single Phase

Battery ... 7 AmpHr 12 VDC x 2

Max Gate Capacity ... 2000 lbs. 45'

Max Operating Speed ... 12" per second

Battery Backup Operation ... 100 Full Cycles (1000 lbs. / 20' gate)

Max Duty Cycle ... 100% Continuous Cycle

Operating Temperature ... - 4° F to + 158° F

7 YEAR RESIDENTIAL / 5 YEAR COMMERCIAL WARRANTY