VIKING ACCESS SYSTEMSTM COMPACT AND POWERFUL DC POWER AUTOMATION







residential **SLIDE GATE OPERATOR** Class I, Class III, and Class IV Vehicular Gate Operator

K-2[™] PRODUCT INFORMATION AND SPECIFICATIONS

The K-2[™] slide gate operator raises the bar in quality for the residential market. This machine operates a highly efficient direct motor drive which allows operation at 100% duty cycle. This assures efficiency and reliability. The fail-safe, fail-secure options of the K-2[™] gate operator allows it to handle gates up to 650 lbs. in conformance with UL 325 and UL 991 Type I, III and IV. This operator is UL Listed 18TC UL325 and UL991.



On-board lightening protection



Soft-stop - Soft-start with Intelligent Obstruction Detection



Innovative Fine Tune Adjustment for the end of gate travel (down to 1/8")



Easy access to limit switch

Built in optional auto-open feature in case of power failure

120/220 VAC single phase power source

Fail-Safe / Fail-Secure

Back-driveable unit features direct drive mechanism



800.908.0884 vikingaccess.com

Operational Voltage ... 24 VDC with 1/2 H.P. Motor **Main Power Source** ... 120 / 220 VAC Single Phase Battery ... 7 AmpHr 12 VDC x 2 **Max Gate Capacity** ... 650 lbs. 27' Max Operating Speed ... 12" per second **Battery Backup Operation** ... 100 Full Cycles (650 lbs. / 20' gate) Max Duty Cycle ... 100% Continuous Cycle **Operating Temperature** ... - 4° F to + 158° F

5 YEAR RESIDENTIAL WARRANTY