

VIKING ACCESS SYSTEMS™

EFFICIENT TECHNOLOGY IN SLIDE GATE OPERATION



residential and commercial


SLIDE GATE OPERATOR

Class I, Class II, Class III, and Class IV Vehicular Gate Operator




L-3™ PRODUCT INFORMATION AND SPECIFICATIONS


The L-3™ gate operator has the capacity to operate slide gates up to 1200 lbs. and 40 feet in length at 100% duty cycle under extreme conditions. It's efficient mechanism provides a solution for high traffic commercial slide gate applications. The Viking L-3™ gate operator offers efficiency and technology combined in a single package. This operator is UL Listed 18TC UL325 and UL991.




On-board
lightening protection



Innovative Fine Tune Adjustment
for the end of gate travel
(down to 1/8")



Soft-stop - Soft-start
with Intelligent
Obstruction Detection



Standard loop rack

120/220 VAC
single phase power source

Built in optional
auto-open feature
in case of power failure

Fail-Safe / Fail-Secure

Back-driveable
unit features
direct drive mechanism



800.908.0884
vikingaccess.com



Operational Voltage	... 24 VDC with 1/2 H.P. Motor
Main Power Source	... 120 / 220 VAC Single Phase
Battery	... 7 AmpHr 12 VDC x 2
Max Gate Capacity	... 1200 lbs. 40'
Max Operating Speed	... 12" per second
Battery Backup Operation	... 100 Full Cycles (1000 lbs. / 20' gate)
Max Duty Cycle	... 100% Continuous Cycle
Operating Temperature	... - 4° F to + 158° F

7 YEAR RESIDENTIAL / 5 YEAR COMMERCIAL WARRANTY