

VIKING ACCESS SYSTEMS™

TRANSPARENT SWING GATE AUTOMATION



residential and commercial

**UNDERGROUND GATE OPERATOR**

Class I, Class II, Class III, and Class IV Vehicular Gate Operator



# i-8™ PRODUCT INFORMATION AND SPECIFICATIONS

The answer for an elegant access control is fulfilled with the i-8 gate operator. The discreteness of the installation, the flexibility of operation, the efficiency of automation, and the adaptability of integration makes the i-8 gate operator a perfect solution in situations where aesthetics are required to satisfy the most exquisite taste. This operator is UL Listed 18TC UL325 and UL991.

Key for  
manual release



Single stage,  
efficient  
gearing system



Configurable to  
open left or open right


water resistant  
gear head unit

built-in adjustable  
positive stop



stainless steel  
casing available

Powerful  
and efficient  
water resistant DC motor  
in direct-drive configuration



800.908.0884  
vikingaccess.com



Operational Voltage	... 24 VDC with 1/2 H.P. Motor
Main Power Source	... 120 / 220 VAC Single Phase
Battery	... 7 AmpHr 12 VDC x 2
Max Gate Capacity	... 650 lbs. 12'
Max Operating Speed	... 13-16 seconds per 90°
Battery Backup Operation	... 400 Full Cycles (500 lbs. / 12' gate)
Max Duty Cycle	... 100% Continuous Cycle
Operating Temperature	... - 4° F to + 158° F

3 YEAR RESIDENTIAL / 2 YEAR COMMERCIAL WARRANTY